

# CITIZEN

## For your events - and for the environment

### Energy efficient ticketing



#### Fanfold or roll media

The CL-S400DT can handle fanfold tickets as well as standard roll media for labels or receipts.

#### Easy read LCD panel

The LCD panel allows quick and simple configuration and also flashes red when an error occurs quickly alerting the operator.

#### Environmentally friendly

From production and packaging to utilisation and recycling the CL-S400DT fulfills today's demand for green IT products. The integrated ENERGY STAR® power supply is one of the most efficient at managing power consumption.

## CL-S400DT

Label, Ticketing

### Applications

- Courier
- Healthcare
- Retail
- Logistic / Transport
- Ticketing



Performance ticket and label printing

# CITIZEN



With a USB and serial interface on board the CT-S400DT is a future-proof investment. Ethernet and parallel interfaces are available as options.

## Specifications

| Model                        | CL-S400DT   |
|------------------------------|---|
| Printing Technology          | Direct Thermal  |
| Resolution                   | 203 dpi   |
| Print Speed (maximum)        | 6 inches per second (150 mm/s)  |
| Print Width (maximum)        | 4 inches (104 mm)   |
| Media Width (min to max)     | 0.5 to 4 inches (12.5 to 118 mm)  |
| Roll Size (max), Core Size   | Inside diameter 5 inches (125 mm) Core size 1 inch (25mm)   |
| Media Thickness (min to max) | 63.5 to 254 µm  |
| Media Length (min to max)    | 0.25 to 32 inches (6.35 to 812.8 mm)  |
| Media Sensor                 | Fully adjustable gap, notch and reflective black mark   |
| Main Interface               | Dual Interface Serial (RS-232C), USB (version 2.0, full speed)  |
| Interface                    | Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Ethernet (10/100 BaseT), Parallel (IEEE 1284 compliant)  |
| Mechanism                    | Hi-Lift™ metal mechanism with wide opening head   |
| Control panel                | 4 buttons, 16x2 LCD with 2-colour backlight and sophisticated menu configuration system   |
| Emulations (Languages)       | Datamax® I-Class™ & DMX400™, Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400, Zebra® ZPL-II®, BASIC interpreter for data stream processing and ticketing emulations |

## CL-S400DT

### Label, Ticketing

### Features & Benefits

- Low space requirement - integrated power supply enables clean work station
- ENERGY STAR® compliant
- Small footprint
- Recyclable packaging
- Basic peeler



Compact footprint and metal mechanism

# CITIZEN

## CL-S400DT

### Label, Ticketing

|                                    |  |
|------------------------------------|--|
| <b>Model</b>                       | <b>CL-S400DT</b>   |
| <b>Drivers and software</b>        | Free-of-charge on CD with printer, including support for various platforms |
| <b>Flash (Non-Volatile Memory)</b> | 8 MB total, 1 MB available for user  |
| <b>Size (W x D x H) and Weight</b> | 206 x 149 x 150mm, 2.68 Kg (excluding roll holder)                         |
| <b>Cutter</b>                      | Guillotine type, Dealer Installable  |
| <b>Warranty</b>                    | 2 years on printer. 6 months or 30 Kms on printhead                        |

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0