

CITIZEN

Compact receipt and label printing

Supports label printing

CT-S281L

POS, Receipt printer (thermal 2 inch / 58 mm)

Applications

- Healthcare
- Hospitality
- Journal
- Kitchen
- Retail



Label version

Label printing has never been so easy. Just connect to your PC and print on standard 2 inch labels.

2-Dimensional Barcode

Unique in its class the CT-S281L is equipped with 2-dimensional barcode.

Low voltage & autocutter

The CT-S281L is CITIZEN's first low-voltage-operated POS printer equipped with an auto cutter.

CITIZEN

CT-S281L

POS, Receipt printer (thermal 2 inch / 58 mm)

Features & Benefits

Specifications

Model	CT-S281L
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	60 mm/sec.
Print Width (maximum)	48 mm
Media Width (min to max)	58 mm
Media Thickness (min to max)	60 to 100 ?m
Media Length (min to max)	25 mm/label (min.)
Media Sensor	Paper end
Main Interface	Dual Interface Serial (RS-232C), USB (version 1.1)
Power supply	DC/V
Reliability	40 million pulse or 20 Km. 400,00 cuts (with label paper)
Emulations (Languages)	ESC/POS™
Drivers and software	Free-of-charge from website, including support for various platforms
Size (W x D x H) and Weight	106x180x105 mm, 0,63 Kg + 0,24 Kg Power supply
EMC and safety standards	CE, TUV, UL, C-UL, FCC class B, VCCI

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

