# SECURE. FAST. PLUG & PLAY.



**EBA-40** 

JCM introduces the next generation EBA, the highly reputed European Bill Acceptor. The EBA-40 allows plug & play upgrade from the EBA-3x series, one of the most widely used bill validators in its class in Europe. The state-of-the-art sensor technology with 8 wavelengths of LEDs captures 10 times more precise data compared to EBA-3x, providing the best security against counterfeits. In addition, the faster processing speed and the industry's best anti-phishing mechanism of EBA-40 Bill Acceptor ensure the unbeatable cost-performance ratio and the long-lasting customer satisfaction.

# **FEATURES**

- Plug & Play upgrade from EBA-3x
- State-of-the-art sensing technology
- Industry's best anti-phishing mechanism
- Optional BARCODE Sensor
- Multiple interfaces
- Multiple protocols

# BENEFITS

- 98%+ acceptance rate
- Field retrofittable without hassles
- Low cost of ownership
- Reads TITO
- TTL, Photo Coupler, RS232, USB
- ID-003, ID-008, ccTalk, MDB



#### **BANKNOTE SIZE**

- Width: 60 85 mm
- Length: 110 181 mm head alone
  110 160 mm with SD3 stacker

## **ACCEPTANCE RATE**

• No less than 98%

## **VALIDATION SPEED**

- Approx 1.5 sec (head alone)
- Approx 3.5 sec (with SD3 stacker)

#### **ESCROW**

• For 1 banknote

# SUPPORTED PROTOCOLS

• ID-003 Serial, ID-008 USB, ccTalk, MDB

## STACKER CAPACITY

400 notes

## POWER REQUIREMENTS

• 12/24VDC +/-5%

## DIMENSIONS (WxDxH)

- EBA-40 Head Unit: 115 x 225 x 86 mm, including bezel
- EBA-40-SD3: 115 x 225 x 317 mm, including bezel

## WEIGHT

EBA-40 Head: 1 kgEBA-40-SD3: 2.5 kg

## **APPROVALS**

• CE

#### **NEW SENSING TECHNOLOGY**

- Super-precise 8 wavelengths of chip on board LEDs in bilaterally symmetric layout
- Sensor resolution and LED stability are 4 times better\*
- Lenses sealed and protected against dust and liquid

\*In comparison to the older product



Bezel connector

