

3, 4 INCH PANEL PRINTER

PORTI-P340, P440



Porti-P340



Porti-P440

Features

- Ultra small size rack mount printer.
- Very silent printing thru direct thermal printing method
- High speed(50mm/sec)
- UART or TTL interface.
- Support text and graphic printing.
- Support bit-image (logo) download.
- Easier paper loading by CLAMSHELL design.
- Easier maintenance with self-diagnostics.



WOOSIM Panel printer series

Specification

Model	P340	P440
Printing method	Direct thermal line printing	
Characters per line	64cpl (MAX)	92cpl (MAX)
Characters size	Eng : 9x24 dots, 12x24 dots Kor : 16x24 dots [24x24 dots]	
Optional Characters	Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin9 and Others upon request.	
Resolution	203 dpi, 8 dots/mm	
Print width	3-inch (72mm, 576 dots)	4-inch (104mm, 832 dots)
Printing speed	50 mm/sec (MAX)	50 mm/sec (MAX)
Dimensions	110 x 77.7 x 49.1 mm	143 x 77.7 x 49.1 mm
Weight	177g	227g
Interface	· UART(RS-232C or TTL)	
Paper supplied	Thermal roll paper (80mm wide, 40Ø)	Thermal roll paper (113mm wide, 40Ø)
	Paper thickness : 60±5µm	
Barcodes	1-dimension:Code128, EAN 128, Code39, I2/5, Code93, UPC, EAN, KAN, JAN, CODABAR 2-dimension:PDF417, QR Code, DATA Matrix	
Driver	Microsoft Windows XP / VISTA / 7 , Windows CE, Linux, Android OS driver compatible	
Input power	9VDC, Standby 60mA and MAX 3A	

Applications

Test & Measurement, Transportation, Health care, ATM, Coupon, Self service, Kiosks, Electronic voting systems.

